# SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

#### **Product identifier**

Chemical Name CAS No. Trade Name Product Code Mixture Mixture RGS Labs FW1 Wash & Wax SP-500753, SP-500753-1,SP-500753-1HOME, SP-500753-2.01, SP-500753HOME, , SP-500872, SP-500872-1.01,SP-500973

Relevant identified uses of the substance or mixture and uses advised against Identified Use(s) Automotive Ca

Uses Advised Against

Company Identification

Telephone Fax E-Mail (competent person)

Emergency telephone number Emergency Phone No. 500872-1.01,SP-500973 vised against Automotive Care Product None

Spray Products Corporation P.O. Box 737 Norristown, PA 19404

(610) 277-1010 (610) 277-4390 johnd@sprayproducts.com

Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

### **SECTION 2: HAZARDS IDENTIFICATION**

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200) Label elements Hazard Symbol Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1



Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Keep away from heat/sparks/open flames/hot surfaces No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
Wear protective gloves/protective clothing/eye protection/face protection.
Use only outdoors or in a well-ventilated area.
Avoid breathing spray.
Wash hands and exposed skin after use.
Keep out of reach of children.

Signal word(s) Hazard Statement(s)

Precautionary Statement(s)

### Other hazards

Harmful to aquatic life.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredient(s)	%W/W *	CAS No.	Hazard classification
Petroleum Distillates	5 - 20	various	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Propane	5 - 10	74-98-6	Flam. Gas 1, H220 Press. Gas (*)

#### Additional Information - None

\* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES



#### Description of first aid measures

Inhalation	Move person to fresh air. If breathing is laboured, administer oxygen. If symptoms develop, obtain medical attention.
Skin Contact	Wash affected skin with soap and water. If symptoms develop, obtain medical attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Do not give anything by mouth to an unconscious person. Do NOT induce vomiting.
Most important symptoms and effects, both acute and delayed	May be fatal if swallowed and enters airways. Will cause skin irritation. Vapours may cause drowsiness and dizziness.
Indication of any immediate medical attention and special treatment needed	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

# **SECTION 5: FIRE-FIGHTING MEASURES**

Extinguishing Media	
-Suitable Extinguishing Media -Unsuitable Extinguishing Media	Extinguish with carbon dioxide, dry chemical, foam or waterspray. Do not use water jet.
Special hazards arising from the substance or mixture	Highly flammable vapour (flash point below 23°C).
Advice for fire-fighters	A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Avoid breathing gas/spray. Avoid contact with skin and eyes.
Environmental precautions	Prevent liquid entering sewers, basements and work pits.
Methods and material for containment and cleaning up	Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.
Reference to other sections	None
Additional Information	None
SECTION 7: HANDLING AND STORAGE	

Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.
Conditions for safe storage, including any incompatib	ilities
-Storage temperature	Keep in a cool, well ventilated place. Store at temperatures not exceeding 50°C / 122 °F.
-Incompatible materials	This product should be stored away from sources of strong heat or oxidizing chemicals.

## Specific end use(s)

Automotive Care Product

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Occupational Exposure Limits**

		(8hr TWA)		(ST		
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
Heptane, branched, cylic and linear	426260-76-6	500 ppm*	1500 mg/m <sup>3</sup>			*n-heptane
C9-C15 Alkanes & Cycloalkanes	Mixture		1200 mg/m <sup>3</sup>			
Propane	74-98-6	1000 ppm	Aspyx.#			#

<sup>#</sup>Assure minimum oxygen content of work atmosphere.

### **Recommended monitoring method**

#### **Exposure controls**

Appropriate engineering controls

#### Personal protection equipment

Eye/face protection



Skin protection (Hand protection/ Other)

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1550 (Naphthas)

Use only with adequate ventilation to keep exposures (airborne levels of dust, fume, vapour etc) below recommended exposure limits.

Wear protective eyewear (goggles, face shield, or safety glasses).

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



Respiratory protection



Thermal hazards

Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Not normally required. Use gloves with insulation for thermal protection, when needed.

**Environmental Exposure Controls** 

None known

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

Appearance Color. Odor Odor Threshold (ppm) pH (Value) Melting Point (°C) / Freezing Point (°C) Boiling point/boiling range (°C): Flash Point (°C) **Evaporation Rate** Flammability (solid, gas) **Explosive Limit Ranges** Vapor pressure (Pascal) Vapor Density (Air=1) Density (g/ml) Solubility (Water) Solubility (Other) Partition Coefficient (n-Octanol/water) Auto Ignition Point (°C) Decomposition Temperature (°C) Kinematic Viscosity (cSt) Explosive properties Oxidizing properties

Liquid / Liquefied gas Clear Petroleum spirit Not available Not available Not available Not available -104 (Propane) Not available Extremely flammable 2.1% - 9.5% v/v (Propane) ca. 95 x  $10^4$  (Propane) ca. 1.56 @ 0°C (Propane) Not available Not available Not available Not available 450 (Propane) Not available <20 Not explosive. Not oxidising.

#### Other information

### SECTION 10: STABILITY AND REACTIVITY

Reactivity Chemical stability Possibility of hazardous reactions Conditions to avoid

Incompatible materials

Stable under normal conditions. Stable. None anticipated. Avoid contact with heat and ignition sources.

Not available

This product should be stored away from sources of strong heat or oxidizing chemicals.

Hazardous decomposition product(s)

None known

## SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity

Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 = 65 - 103 mg/L (Vapour), 4-hr. rat May cause drowsiness or dizziness.

Irritation/Corrosivity	Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause eye irritation.
Sensitisation	It is not a skin sensitiser.
Repeated dose toxicity	NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects) LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects) May cause drowsiness or dizziness.
Carcinogenicity	No data. It is unlikely to present a carcinogenic hazard to man.
Mutagenicity	There is no evidence of mutagenic potential.
Reproductive toxicity	None anticipated
Propane (CAS# 74-98-6): Acute toxicity	Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)
Irritation/Corrosivity	No evidence of irritant effects from normal handling and use.
Sensitisation	It is not a skin sensitiser.
Repeated dose toxicity	NOAEC: ≥19678 mg/m3 (28-day, rat, Systemic effects) LOAEC: 21641 mg/m3 (28-day, rat, effects: Body weight)
Carcinogenicity	No data. It is unlikely to present a carcinogenic hazard to man.
Mutagenicity	There is no evidence of mutagenic potential.
Reproductive toxicity	None anticipated

# **SECTION 12: ECOLOGICAL INFORMATION**

### Aquatic toxicity:

Heptane. branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:				
Short term	LL50 (96 hour): >13.4 mg/L ( <i>Oncorhynchus mykiss</i> ) EL50 (48 hour): 3 mg/l ( <i>Daphnia magna</i> , mobility) EC50 (96 hour): 13 mg/l ( <i>Pseudokirchnerella subcapitata</i> )			
Long Term	NOELR (28 days) 1.5 mg/l <i>(Fish</i> ) QSAR LOEC (21 days): 0.32 mg/l ( <i>Daphnia magna</i> ) NOEL (96 hour) 6.3 mg/l ( <i>Algae)</i>			

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

## **SECTION 14: TRANSPORT INFORMATION**

	U.S. DOT	Sea transport <u>(IMDG)</u>	Air transport <u>(ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

## **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

#### Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

	Chemical Name CAS No.			Typical %wt.		RQ (Pounds)	
	Sodium Nitrite 7632-00-0			0.5		100	
SARA 3	☐ Immediate (acute) ☐ Chron			Chronic	nic (delayed)		
SARA 313 - Toxic Chemicals (40 CFR 372):							
	Chemical Name			CAS No.		Typical %wt.	
	Sodium Nitrite			7632-00-0		0-0	0.5
SARA 302 - Extremely Hazardous Substances(40 CFR 355):							
	Chemical N	CAS No. Typic		al %wt.	TPQ (pounds)		
	None						
California Proposition 65 List:							
	Chemical Name		CAS N	CAS No.		Type of Toxicity	
	None						

# **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: 1-16. Date of preparation: September 23, 2014

Hazard Statement(s) and Risk Phrases Listed in:

#### Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapour.
- H272: May intensify fire; oxidiser.
- H301: Toxic if swallowed.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H336: May cause drowsiness or dizziness.
- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

#### Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.