

RGS Labs FW1 Wash & Wax

SAFETY DATA SHEET

According to Canada's Hazardous Products Regulations (HPR) SOR/2015-17

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	RGS Labs FW1 Wash & Wax
Product Code	10-500862 500952

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Automotive Care Product
Uses Advised Against	None

Company Identification	Spray Products Corporation P.O. Box 737 Norristown, PA 19404 Pizazz International Promotions, Inc 106-950 Alsgard St Kelowna, BC V1X 7J2 Canada
Telephone	(610) 277-1010
Fax	(610) 277-4390
E-Mail (competent person)	sds@sprayoproducts.com

Emergency telephone number

Emergency Phone No.	Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)
---------------------	---

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

HPR/WHIMIS 2015/GHS Classification

Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



DANGER

Signal word(s)

Hazard Statement(s)

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

RGS Labs FW1 Wash & Wax

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Use only outdoors or in a well-ventilated area.
 Avoid breathing spray.
 Wash hands and exposed skin after use.
 Keep out of reach of children.
 Harmful to aquatic life.

Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredient(s)	%W/W *	CAS No.	Hazard classification
Petroleum Distillates	5 - 10	426260-76-6	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Distillates (petroleum), hydrotreated light	5 - 10	64742-47-8	Asp. Tox. 1; H304
Propane	5 - 10	74-98-6	Flam. Gas 1, H220 Press. Gas (*)

Additional Information - None

* The exact percentage withheld as a trade secret.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation	Move person to fresh air. If breathing is laboured, administer oxygen. If symptoms develop, obtain medical attention.
Skin Contact	Wash affected skin with soap and water. If symptoms develop, obtain medical attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Do not give anything by mouth to an unconscious person. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed May be fatal if swallowed and enters airways. Will cause skin irritation. Vapours may cause drowsiness and dizziness.

RGS Labs FW1 Wash & Wax

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or waterspray. Do not use water jet.

Special hazards arising from the substance or mixture

Highly flammable vapour (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Avoid breathing gas/spray. Avoid contact with skin and eyes.

Environmental precautions

Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Keep in a cool, well ventilated place. Store at temperatures not exceeding 50°C / 122 °F.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

Specific end use(s)

Automotive Care Product

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		OEL (Canada)	TLV (ACGIH)	OEL (Canada)	TLV (ACGIH)	
Heptane, branched, cyclic and linear	426260-76-6	400 ppm*	1500 mg/m ³	500 ppm*	-----	*n-heptane
C ₉ -C ₁₅ Alkanes & Cycloalkanes	Mixture	-----	1200 mg/m ³	-----	-----	
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#

*Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1550 (Naphthas)

Exposure controls

Appropriate engineering controls

Use only with adequate ventilation to keep exposures (airborne levels

RGS Labs FW1 Wash & Wax

of dust, fume, vapour etc) below recommended exposure limits.

Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid / Liquefied gas
Color.	Clear
Odor	Petroleum spirit
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. 95×10^4 (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	<20
Explosive properties	Not explosive.
Oxidizing properties	Not oxidising.
Other information	Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.

RGS Labs FW1 Wash & Wax

Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

Hazardous decomposition product(s)

None known

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity

Oral: LD50 >5 g/kg-bw
Dermal: LD50 >2 g/kg-bw
Inhalation: LC50 = 65 - 103 mg/L (Vapour), 4-hr. rat
May cause drowsiness or dizziness.

Irritation/Corrosivity

Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause eye irritation.

Sensitisation

It is not a skin sensitiser.

Repeated dose toxicity

NOAEC: 12350 mg/m³ (2 yr, inhal., rat, Systemic effects)
LOAEC: 1650 mg/m³ (2 hr, inhal., rat, CNS effects)
May cause drowsiness or dizziness.

Carcinogenicity

No data. It is unlikely to present a carcinogenic hazard to man.

Mutagenicity

There is no evidence of mutagenic potential.

Reproductive toxicity

None anticipated

Propane (CAS# 74-98-6):

Acute toxicity

Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)

Irritation/Corrosivity

No evidence of irritant effects from normal handling and use.

Sensitisation

It is not a skin sensitiser.

Repeated dose toxicity

NOAEC: ≥19678 mg/m³ (28-day, rat, Systemic effects)
LOAEC: 21641 mg/m³ (28-day, rat, effects: Body weight)

Carcinogenicity

No data. It is unlikely to present a carcinogenic hazard to man.

Mutagenicity

There is no evidence of mutagenic potential.

Reproductive toxicity

None anticipated

SECTION 12: ECOLOGICAL INFORMATION

Aquatic toxicity:

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term

LL50 (96 hour): >13.4 mg/L (*Oncorhynchus mykiss*)
EL50 (48 hour): 3 mg/l (*Daphnia magna*, mobility)
EC50 (96 hour): 13 mg/l (*Pseudokirchnerella subcapitata*)

Long Term

NOELR (28 days) 1.5 mg/l (*Fish*) QSAR
LOEC (21 days): 0.32 mg/l (*Daphnia magna*)
NOEL (96 hour) 6.3 mg/l (*Algae*)

RGS Labs FW1 Wash & Wax

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	Land transport (TDG)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

This product has been classified in accordance to CPR Section 12 and the MSDS contains all the information required by the CPR.

Canada (DSL/NDSL) - All chemicals listed.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: February 17, 2017

Hazard Statement(s) and Risk Phrases Listed in:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapour.
- H272: May intensify fire; oxidiser.
- H301: Toxic if swallowed.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H336: May cause drowsiness or dizziness.
- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.